

KEY FEATURES

- Fits through any door
- Stairs not a problem
- Can be built in the room where they are to be used
- Internal light
- Replaceable door Gasket

EXTRA SPEC DETAILS

- Power Required – 13 amp
- Automatic defrost
- Refrigerant – R404a
- Refrigeration system - Fan assisted evaporator & condenser
- Castors standard
- External Finish – Stainless Steel
- Internal Finish - Stainless Steel
- Max Ambient - 43°C / 60% RH



2 / 1 GN Flat Pack Service Cabinets



GM 7/C



GM 14/C



GM 21/C

Model	Dimensions (wxdxh) mm	Temperature	Net Weight Kg	Capacity Litres / cu ft	Doors	Shelves
GM 7/C	720 x 800 x 2120	-2 / +8°C	120	700/24.7	1	3
GM 14/C	1440 x 800 x 2120	-2 / +8°C	190	1400/49.4	2	6
GM 21/C	2160 x 800 x 2120	-2 / +8°C	295	2100/74.2	3	9
GB 7/C	720 x 800 x 2120	-10 / -25°C	130	700/24.7	1	3
GB 14/C	1440 x 800 x 2120	-10 / -25°C	200	1400/49.4	2	6
GB 21/C	2160 x 800 x 2120	-10 / -25°C	305	2100/74.2	3	9

INSTALLATION SERVICE AVAILABLE - POA MINIMUM HEIGHT OF INSTALL PURPOSES 2290MM